

**Torque screwdriver with scale, maximum torque: 500cNm****Order data**

Order number	659949 500
GTIN	4580125347571
Item class	66F

Description**Version:**

Setting using a micrometer scale. Profiled light alloy handle.

Function:

When the set torque is reached the screwdriver triggers and signals clearly (audibly and perceptibly). It is then again immediately ready for use.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Technical description

Display	analogue
Ø	40 mm
maximum torque	500 cNm
Scale graduation, 1 graduation =	2.5 cNm
Torque measuring accuracy	±6 %
Bit socket	F 6.3
Torque range	100 - 500 cNm
Torque range	1 - 5 Nm
Reversible reading	cNm

Standard	DIN EN ISO 6789
Weight	436 g
Measurement process	Torque
Connection format	Bit holder 1/4 inch
Overall length L	200 mm
Trigger principle	mechanical short-travel release
Setting the trigger value	with adjustment scale
Feedback	triggering
Adjustable trigger value	adjustable
Calibration	O3
Direction of tightening	For right- and left-hand tightening
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	akustisk
Release signalling	haptisk
Measurement technology	mechanical
Type of product	Torque screwdriver

Services

DAkkS calibrationTorque wrench clockwise / anti-clockwise maximum torque 1000/2 N·m	020040 1000/2
CalibrationTorque screwdrivers, clockwise / anti-clockwise maximum torque 0,04-20/2 N·m	020260 0,04-20/2